



SAFETY DATA SHEET

minus DK®

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : minus DK®
Product code : 13074
Internal code : 13074
Date of issue/ Date of revision : 12/11/2023
Date of previous issue : 12/11/2023
Version : 10.03
Product description : Mixture
Physical state : Liquid.
Chemical identity : Not available.
UFI : 74P0-P0M8-4007-JCQ8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Petrochemical industry: Fuel additive.

1.3 Details of the supplier of the safety data sheet

UK Supplier : Innospec Limited
Innospec Manufacturing Park
Oil Sites Road, Ellesmere Port
Cheshire CH65 4EY
United Kingdom

Telephone no.: : +44 (0)151 355 3611
Fax no. : +44 (0)151 356 2349
e-mail address of person responsible for this SDS : sdsinfo@innospecinc.com

EU Supplier : Innospec Limited
Boite Postale 19, F-55300 St. Mihiel
Han-sur-Meuse, Meuse, France
+ 33 3 2991 7300

1.4 Emergency telephone number

In Europe, Middle East, Africa, Asia Pacific and South America
24 hour / 7 day emergency response for our products is
provided by the NCEC CARECHEM 24 global network



The main regional centres are listed here in Section 1. Other local contact numbers for specific language support in Asia Pacific are listed in Section 16.

Country information

Europe (all countries, all languages)

Emergency telephone number

: +44 (0) 1235 239 670

Location

London, UK

Date of issue/Date of revision : 12/11/2023

1/18

minus DK®

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Middle East, Africa (Arabic, French, English , Portuguese, Farsi) : +44 (0) 1235 239 671 London, UK

Asia Pacific (all countries except China) : +65 3158 1074 Singapore

China : 400 120 6011 Beijing China

Brazil : +55 11 3197 5891 Brazil

Mexico : +52 555 004 8763 Mexico

In USA, Canada and North America, 24 h/7 days of emergency response for our product is provided by the CHEMTREC(R) Emergency Call Center based in the USA.

Country information : **Emergency telephone number**

USA : 800 424 9300

Canada, Puerto Rico, Virgin Islands : +1 800 424 9300

In case of difficulty using the toll-free number, or for ships at sea, call : +1 703 527 3887

See section 16.



Indicates information that has changed from previously issued version.

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

STOT SE 3, H336

Asp. Tox. 1, H304

Aquatic Chronic 2, H411

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H304 - May be fatal if swallowed and enters airways.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.

Supplemental label elements : Repeated exposure may cause skin dryness or cracking.

Precautionary statements

General : Not applicable.

Prevention : P273 - Avoid release to the environment.
P261 - Avoid breathing vapour.

Response : P391 - Collect spillage.
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

minus DK®

SECTION 2: Hazards identification

Hazardous ingredients : Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	REACH #: 01-2119463583-34 EC: 918-811-1 CAS: 64742-94-5 Index: 649-424-00-3	≥75 - ≤90	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1] [2]
naphthalene	EC: 202-049-5 CAS: 91-20-3 Index: 601-052-00-2	<1	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 490 mg/kg M [Acute] = 1 M [Chronic] = 1	[1] [2]
2-ethylhexanoic acid	REACH #: 01-2119488942-23 EC: 205-743-6 CAS: 149-57-5 Index: 607-230-00-6	<0.3	Repr. 1B, H360D See Section 16 for the full text of the H statements declared above.	-	[1]

Additional CAS # used in National Inventories

Solvent naphtha (petroleum), heavy arom.	-	64742-94-5
naphthalene	-	91-20-3
2-ethylhexanoic acid	-	149-57-5

Additional information

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

[Type](#)

minus DK®

SECTION 3: Composition/information on ingredients

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

Our REACH (pre-) registrations DO NOT cover the following:

1. The manufacture of these products by our company outside the EU unless covered by the Only Representative provisions, and
 2. The importation of these products into Europe by other companies. Re-importation by other companies is not covered by our (pre-) registrations
- Customers and other third parties importing and/or re-importing our products into Europe will need either:
- Their own (pre-) registration for substances contained in the imported product, or constituent monomers (imported above 1 tonne per year and >2% by weight) in the case of imported polymers, or
 - In the case of importation only, to make use of the "Only Representative" provisions, if available.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Skin contact | : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : Get medical attention immediately. Call a poison center or physician. Remove dentures if any. Wash out mouth with water. Stop if the exposed person feels sick as vomiting may be dangerous. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- | | |
|---------------------|----------------------------------------------------------------------------------------------------|
| Eye contact | : No known significant effects or critical hazards. |
| Inhalation | : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. |
| Skin contact | : Defatting to the skin. May cause skin dryness and irritation. |
| Ingestion | : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. |

Over-exposure signs/symptoms

- | | |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Eye contact | : No specific data. |
| Inhalation | : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness |

minus DK®

SECTION 4: First aid measures

- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

minus DK®

SECTION 6: Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- Storage** : Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

minus DK®

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
Solvent naphtha (petroleum), heavy arom. 1,2,4-trimethylbenzene	Supplier/Manufacturer (Europe, 2015). EU HSPA (RCP Aromatic solvents 180 - 215): 151 mg/m ³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 1/2020). [trimethylbenzenes, all isomers or mixtures] TWA: 25 ppm 8 hours. TWA: 125 mg/m ³ 8 hours.
naphthalene	EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values TWA: 10 ppm 8 hours. TWA: 50 mg/m ³ , 0 times per shift, 8 hours.
cumene	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 250 mg/m ³ , 0 times per shift, 15 minutes. STEL: 50 ppm, 0 times per shift, 15 minutes. TWA: 25 ppm, 0 times per shift, 8 hours. TWA: 125 mg/m ³ , 0 times per shift, 8 hours.
o-Xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-, m-, p- or mixed isomers] Absorbed through skin. STEL: 441 mg/m ³ , 0 times per shift, 15 minutes. TWA: 50 ppm, 0 times per shift, 8 hours. TWA: 220 mg/m ³ , 0 times per shift, 8 hours. STEL: 100 ppm, 0 times per shift, 15 minutes.
Solvent naphtha (petroleum), heavy arom. methanol	Supplier/Manufacturer (Europe, 2015). EU HSPA (RCP Aromatic solvents 180 - 215): 151 mg/m ³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 333 mg/m ³ 15 minutes. STEL: 250 ppm 15 minutes. TWA: 266 mg/m ³ 8 hours. TWA: 200 ppm 8 hours.
isopropanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). STEL: 1250 mg/m ³ , 0 times per shift, 15 minutes. STEL: 500 ppm, 0 times per shift, 15 minutes. TWA: 999 mg/m ³ , 0 times per shift, 8 hours. TWA: 400 ppm, 0 times per shift, 8 hours.
sulphuric acid	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 0.05 mg/m ³ 8 hours. Form: Solution
mesitylene	EH40/2005 WELs (United Kingdom (UK), 1/2020). [trimethylbenzenes, all isomers or mixtures] TWA: 25 ppm, 0 times per shift, 8 hours. TWA: 125 mg/m ³ , 0 times per shift, 8 hours.
sulphur dioxide	EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 2.7 mg/m ³ 15 minutes. STEL: 1 ppm 15 minutes. TWA: 1.3 mg/m ³ 8 hours. TWA: 0.5 ppm 8 hours.
chloromethane	EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 210 mg/m ³ , 0 times per shift, 15 minutes. STEL: 100 ppm, 0 times per shift, 15 minutes. TWA: 50 ppm, 0 times per shift, 8 hours. TWA: 105 mg/m ³ , 0 times per shift, 8 hours.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance

minus DK®

SECTION 8: Exposure controls/personal protection

documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	DNEL	Long term Dermal	12.5 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	151 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	7.5 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	32 mg/m ³	Consumers	Systemic
	DNEL	Long term Oral	7.5 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	2.1 mg/kg bw/day	General population	Systemic
	DMEL	Long term Inhalation	3.25 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	10.2 mg/m ³	General population	Systemic
	DMEL	Long term Dermal	23.4 mg/ kg bw/day	Workers	Systemic
	DMEL	Long term Dermal	42.4 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.57 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	25 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	25 mg/m ³	Workers	Local
	DNEL	Long term Dermal	3.57 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	25 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	25 mg/m ³	Workers	Systemic
naphthalene	DNEL	Long term Oral	1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.5 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	14 mg/m ³	Workers	Systemic
2-ethylhexanoic acid					

PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
naphthalene	PNEC	Fresh water	2.4 µg/l	-
	PNEC	Marine	0.24 µg/l	-
	PNEC	Sewage Treatment Plant	2.9 mg/l	-
	PNEC	Fresh water sediment	67.2 µg/kg dwt	-
	PNEC	Marine water sediment	67.2 µg/kg dwt	-
2-ethylhexanoic acid	PNEC	Soil	53.3 µg/kg dwt	-
	PNEC	Fresh water	0.017 mg/l	-
	PNEC	Marine	0.0017 mg/l	-
	PNEC	Sewage Treatment Plant	10 mg/l	-
	PNEC	Fresh water sediment	0.28 mg/kg dwt	-

minus DK®

SECTION 8: Exposure controls/personal protection

	PNEC	Marine water sediment	0.028 mg/kg dwt	-
	PNEC	Soil	0.047 mg/kg dwt	-

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: splash goggles

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Viton®
1 - 4 hours (breakthrough time): nitrile rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A)

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state : Liquid. [Clear to slightly hazy liquid.]
Colour : Amber. Clear to slightly hazy
Odour : Aromatic.
Odour threshold : Not available.
pH : Not applicable.
Melting point/freezing point : Not available.
Initial boiling point and boiling range : Lowest known value: 178 to 215°C (352.4 to 419°F)(Solvent naphtha (petroleum), heavy arom.).
Flash point : Closed cup: >60°C (>140°F) [Pensky-Martens]

minus DK®

SECTION 9: Physical and chemical properties

Evaporation rate	: 0.05 (Solvent naphtha (petroleum), heavy arom.) compared with butyl acetate
Flammability (solid, gas)	: Not available.
Burning time	: Not applicable.
Burning rate	: Not applicable.
Upper/lower flammability or explosive limits	: Greatest known range: Lower: 0.6% Upper: 7% (Solvent naphtha (petroleum), heavy arom.)
Vapour pressure	: Highest known value: 0.1 kPa (0.8 mm Hg) (at 20°C) (Solvent naphtha (petroleum), heavy arom.).
Vapour density	: Highest known value: 4.6 to 5.5 (Air = 1) (Solvent naphtha (petroleum), heavy arom.).
Relative density	: Not available.
Density	: 0.9 g/cm ³ [15°C (59°F)]
Solubility(ies)	:
Miscible with water	: No.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Lowest known value: 425°C (797°F) (Solvent naphtha (petroleum), heavy arom.).
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): 3.82 mm ² /s (3.82 cSt)
Explosive properties	: Not available.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

Pour point : -30°C

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Incompatible with fluorine.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

minus DK®

SECTION 11: Toxicological information

Product/ingredient name	Test	Species	Result type	Dose
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	-	Rat	LC50 Inhalation Vapour	>590 mg/m ³
naphthalene	-	Rabbit	LD50 Dermal	>2 mL/kg
	-	Rabbit	LD50 Dermal	>2000 mg/kg
	-	Rat	LDLo Oral	5 mL/kg
	-	Rat	LC50 Inhalation Vapour	>340 mg/m ³
2-ethylhexanoic acid	-	Rabbit	LD50 Dermal	>2000 mg/kg
	-	Rat	LD50 Oral	490 mg/kg
	-	Rabbit	LD50 Dermal	>2000 mg/kg
	-	Rat	LD50 Oral	3640 mg/kg

Irritation/Corrosion

Product/ingredient name	Test	Species	Result
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	-	Mammal - species unspecified	Eyes - Mild irritant -
2-ethylhexanoic acid	-	Rabbit	Skin - Mild irritant -
	-	Rabbit	Skin - Mild irritant -

Reproductive toxicity

Product/ingredient name	Test	Species	Result	Dose
2-ethylhexanoic acid	-	Rat - Male, Female	-	Oral: 600 mg/kg

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Date of issue/Date of revision : 12/11/2023

11/18

minus DK®

SECTION 11: Toxicological information**Short term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Long term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.**Carcinogenicity** : No known significant effects or critical hazards.**Mutagenicity** : No known significant effects or critical hazards.**Teratogenicity** : No known significant effects or critical hazards.**Developmental effects** : No known significant effects or critical hazards.**Fertility effects** : No known significant effects or critical hazards.**11.2 Information on other hazards****11.2.1 Endocrine disrupting properties**

No known significant effects or critical hazards.

11.2.2 Other information

Not available.

SECTION 12: Ecological information**12.1 Toxicity**

Product/ingredient name	Test	Species	Exposure	Result
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	-	Algae	72 hours	Acute EC50 1 to 3 mg/l
naphthalene	-	Daphnia	48 hours	Acute EC50 3 to 10 mg/l
	-	Fish	96 hours	Acute LC50 2 to 5 mg/l
	-	Daphnia - Water flea - Daphnia magna	48 hours	Acute EC50 1.96 mg/l Fresh water
	-	Crustaceans - Daggerblade grass shrimp - Palaemonetes pugio	48 hours	Acute LC50 2350 µg/l Marine water
	-	Fish - Oncorhynchus mykiss	96 hours	Acute LC50 1.6 mg/l
	-	Crustaceans - Fiddler crab - Uca pugnax - Adult	3 weeks	Chronic NOEC 0.5 mg/l Marine water
	-	Fish - Mozambique tilapia - Oreochromis mossambicus	60 days	Chronic NOEC 1.5 mg/l Fresh water
	-	Daphnia	48 hours	EC50 85.4 mg/l
2-ethylhexanoic acid	-			

12.2 Persistence and degradability

Product/ingredient name	Test	Result
2-ethylhexanoic acid	- 301D Ready Biodegradability - Closed Bottle Test	83 % - Readily - 20 days 76 % - Readily - 10 days

minus DK®

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	-	-	Inherent
2-ethylhexanoic acid	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Hydrocarbons C10, Aromatics, <1% Naphthalene, [Solvent naphtha (petroleum), heavy arom.]	2.8 to 6.5	<100	low
naphthalene	3.4	36.5 to 168	low
2-ethylhexanoic acid	2.7	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Endocrine disrupting properties

No known significant effects or critical hazards.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.





Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

minus DK®

SECTION 13: Disposal considerations**SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Solvent naphtha (petroleum), heavy arom.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Solvent naphtha (petroleum), heavy arom.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Solvent naphtha (petroleum), heavy arom.). Marine pollutant (Solvent naphtha (petroleum), heavy arom., naphthalene)	Environmentally hazardous substance, liquid, n.o.s. (Solvent naphtha (petroleum), heavy arom.)
14.3 Transport hazard class(es)	9 	9 	9 	9 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Additional information	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Hazard identification number 90 Limited quantity 5 L Special provisions 274, 335, 601, 375 Tunnel code (-)	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Special provisions 274, 335, 375, 601	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F Special provisions 274, 335, 969	
14.6 Special precautions for user				
14.7 Maritime transport in bulk according to IMO instruments				

minus DK®

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.
on the manufacture,
placing on the market
and use of certain
dangerous substances,
mixtures and articles

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not available.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Seveso Directive - Reporting thresholds (in tonnes)

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2	200	500

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

National regulations

Chemical Weapons Convention List Schedule I Chemicals :Not listed

Chemical Weapons Convention List Schedule II Chemicals :Not listed

Chemical Weapons Convention List Schedule III Chemicals :Not listed

International lists

Australia inventory (AIIIC) :All components are listed or exempted.

Canada inventory :All components are listed or exempted.

minus DK®

SECTION 15: Regulatory information

China inventory (IECSC)	:At least one component is not listed.
EU REACH Status	:Please contact your supplier for information on the REACH status of this material.
Japan inventory	:Not determined.
Korea REACH Status	:Please contact your supplier for information on the REACH status of this material.
New Zealand Inventory of Chemicals (NZIoC)	:All components are listed or exempted.
Philippines inventory (PICCS)	:At least one component is not listed.
Taiwan REACH Status	:Please contact your supplier for information on the REACH status of this material.
Turkey REACH Status	:Please contact your supplier for information on the REACH status of this material.
United States inventory (TSCA 8b)	:All components are listed or exempted.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
-----------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	Calculation method Calculation method Calculation method

Full text of abbreviated H statements	: H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H301 Toxic if swallowed. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage.
----------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

minus DK®

SECTION 16: Other information

H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H350 May cause cancer.
 H351 Suspected of causing cancer.
 H361d Suspected of damaging the unborn child.
 H370 Causes damage to organs.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

**Full text of classifications
[CLP/GHS]**

: Acute Tox. 3 ACUTE TOXICITY - Category 3
 Acute Tox. 4 ACUTE TOXICITY - Category 4
 Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
 Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
 Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
 Asp. Tox. 1 ASPIRATION HAZARD - Category 1
 Carc. 1B CARCINOGENICITY - Category 1B
 Carc. 2 CARCINOGENICITY - Category 2
 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
 Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
 Flam. Gas 1A FLAMMABLE GASES - Category 1A
 Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2
 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3
 Press. Gas (Comp.) GASES UNDER PRESSURE - Compressed gas
 Repr. 2 REPRODUCTIVE TOXICITY - Category 2
 Skin Corr. 1A SKIN CORROSION/IRRITATION - Category 1A
 Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B
 Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2
 STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
 STOT SE 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1
 STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of printing : 2023-12-11**Date of issue/ Date of revision** : 12/11/2023**Date of previous issue** : 12/11/2023**Version** : 10.03**Emergency contact numbers for local language support in Asia Pacific region**

Country information	Languages supported	Telephone no.:	Location
Australia	English	+61 2 8014 4558	Australia
Bangladesh	Bengali, English	+65 3158 1200	Singapore
China	Mandarin, English	400 120 6011	Beijing China
India	Hindi, English	+65 3158 1198	Singapore
India (local toll free number)	Hindi, English	000800 100 7479	India
Indonesia (local toll free number)	Bahasa Indonesian, English	00780 3011 0293	Indonesia
Japan	Japanese, English	+81 3 4578 9341	Japan

Date of issue/Date of revision : 12/11/2023**17/18**

minus DK®

SECTION 16: Other information

Korea	Korean, English	+65 3158 1285	Singapore
Malaysia	Bahasa Malaysian, English	+60 3 6207 4347	Malaysia
New Zealand	English	+64 9929 1483	New Zealand
Pakistan	Urdu, English	+65 3158 1329	Singapore
Philippines	Tagalog, English	+63 2 8231 2149	Singapore
Sri Lanka	Sinhalese, English	+65 3158 1195	Singapore
Thailand (local toll free number)	Thai, English	001800 1 2066 6751	Thailand
Vietnam	Vietnamese, English	+65 3158 1255	Singapore

Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.